

STM55 - STM70



- Roomy operator ROPS certified platform.
- Fingertip controls for hydraulic functions.
- High flotation 31" tires.
- Three-wheel drive for adverse ground conditions.
- EZ Drive automotive controls provide safe and efficient operation.
- Multi-function LCD display with on board diagnostics and operational guidance.

Specifications		
	STM55	STM70
Lift capacity @ 24" LC	5,500 lbs 2,500 kg	7,000 lbs 3,175 kg
Base operating weight (without forks)*	6,560 lbs 2,976 kg	6690 lbs 3,035 kg
Overall length (without forks)	102" 2,591 mm	105.5" 2,680 mm
Overall width	100" 2,540 mm	
Height to top of overhead guard	96" 2,438 mm	
Turning radius	120" 3,048 mm	123" 3,124 mm

*Base operating weight with 144" mast.

STM55-4W



• 4 Way Multi-Directional •

- Multi-directional feature provides the ability to place long loads in tight spaces.
- One-touch button transitions from standard configuration to 4WAY mode.
- Intuitive steering allows for safe load handling.
- Attaches to existing Sellick mounting kits.

Specifications	
Lift capacity @ 24" load centre	5,500 lbs (2,495 kg)
Base operating weight (without forks)*	8,285 lbs (3,758 kg)
Overall length (without forks)	99" (2,515 mm)
Overall length (with 48" forks)	116" (2,946 mm)
Overall width (standard)	101" (2,565 mm)
Overall width (4 Way)	99" (2,515 mm)
Overall width with 48" forks (4 Way)	115" (2,921 mm)
Height to top of overhead guard	98" (2,489 mm)
Turning radius	120" (3,048 mm)

*Base operating weight with 144" mast.

STM55P



- Unload truck/trailers from one side with the pantograph reach option.
- **Kohler Tier 4, 56 HP diesel engine.**
- Exceptional low end torque.
- No exhaust aftertreatment, diesel particulate filter (DPF) or diesel exhaust fluid (DEF) required.
- Two stage air filtration.
- Cold weather preheat & water separator.

Specifications	STM55P
Lift capacity @ 24" LC	5,500 lbs 2,500kg
Base operating weight (without forks)*	7,590 lbs 3,443 kg
Overall length (without forks)	105.5" 2,680 mm
Overall width	100" 2,540 mm
Height to top of overhead guard	96" 2,438 mm
Turning radius	123" 3,124 mm

*Base operating weight with 144" mast.

All SELLICK Truck-mounted Forklifts meet or exceed all ANSI/ITSDF B56.14 Safety Standards. All SELLICK Operator Compartments and Overhead Guards are ROPS/FOPS Certified.

OPTIONS & ACCESSORIES

- Enclosed cab with heat, wipers and sliding windows
- Cold weather package
- Tilt steering
- Suspension seat
- Engine block heater
- Strobe light
- Hydraulic fork positioning carriage
- Rear view mirrors for added safety
- Custom paint
- Variety of forks for any attachment and application

Sold & Serviced By:



Sellick Equipment Limited
 358 Erie Street North
 Harrow, Ontario, Canada N0R 1G0
 Telephone: 519-738-2255
 Fax: 519-738-3477
 E-mail: sellick@mnsi.net
 Website: www.sellickequipment.com



Because of our constant dedication to product improvement, all specifications are subject to change without notice.



HEAVY DUTY TRUCK MOUNTED FORKLIFTS



ADAPTABLE



VERSATILE



POWERFUL



MULTI-DIRECTIONAL